ELECTRIC GUITAR

AEX520

SERVICE MANUAL




■ CONTENTS

| OVERALL ASSEMBLY | 2 |
|------------------|---|
| PARTS LIST | 3 |
| CIRCUIT DIAGRAM | 4 |
| WIRING | 4 |
| SPECIFICATIONS | 4 |



■ OVERALL ASSEMBLY



■ PARTS LIST

| [| REF NO. | PART NO. | T NO. DESCRIPTION | | REMARKS | QTY | RANK |
|----------|------------|-----------|-----------------------------------|-------------------------|----------------|-----|------|
| | | | OVERALL ASSEMBLY | | AEX520 | | |
| * | A01 | DX809770 | Neck Assembly | | | | |
| | A01a | | Seal | | (QC45770) | | |
| | | | | | (45.5) | | |
| | D01 | | Body | | | | |
| | | | Body | | | | |
| | E01 | 0.4170800 | Tuning Machine Assembly | RM-1271GVR | 1set | | |
| | E02 | 03704070 | Round Head Wood Screw | 2.4X10 GOLD (GL) | 1561 | 6 | |
| | E03 | VQ014700 | | 43mm (Ivory) | | 0 | 02 |
| | E04 | VQ014700 | | BL | | | 02 |
| | E05 | | Oval Head Wood Screw | 2.1X10 FCM3BL (BL) | | | 02 |
| | E10 | | | BL | | 3 | 01 |
| | E10 | | Neck Joint Bushing | | | 4 | 04 |
| | | | Oval Head Tapping Screw | 5.0X45 FCM3BL (BL) | | 4 | |
| | E16 | QC466600 | Bridge Assembly | TP6-3 (GOLD) | | _ | |
| | E17 | QC466700 | Bridge Adjusting Screw | TP6-3S (GOLD) | | 2 | |
| * | E18 | QC466800 | Nut | TP6-3B (GOLD) | | 2 | |
| * | E19 | | Tailpiece Assembly | TP6-1 (GOLD) | | | |
| * | E20 | QC467000 | Tailpiece Column | TP6-1S (GOLD) | | 2 | |
| * | E21 | QC467100 | | TP6-1B (GOLD) | | 2 | |
| | E29 | <u> </u> | Strings | XL-115 | 1set (QC40220) | | |
| | E32 | BB802460 | | GOLD | | 2 | 02 |
| | E33 | EN230130 | Oval Head Wood Screw | 3.0X25 GOLD (GL) | | 2 | 02 |
| | E34 | VB793700 | Spacer | BL | | 2 | 01 |
| * | E36 | QC476800 | Knob | GOLD | VOLUME,TONE | 2 | |
| | E41 | | Back Cover | Electrical (BL) | | | |
| | E42 | CB023450 | Back Cover | Switch (BL) | | | |
| | E43 | EB620020 | Oval Head Wood Screw | 2.7X13 FCM3BL (BL) | | 7 | 03 |
| | | | | ` ' | | | |
| | F01 | | Electrical Unit | | (QC47840) | | |
| | F01a | HS120070 | Variable Resistor | 15A 500K ohm | VOLUME | | |
| | | HS120100 | | 05A 250K ohm | TONE | | |
| | | | Mylar Cap. | 0.022uF 50 K | | | |
| | | QC234900 | Jack | 0.0224. 00.1 | | | |
| | F03 | QA025000 | Pickup Switch | 3-P GOLD | | | |
| | F06 | VA295700 | | BL | | | |
| | F11 | ET800010 | Toothed Lock Washer | A12S | | | |
| | F13 | VB518300 | | BL | | | 05 |
| | F14 | | Oval Head Wood Screw | 2.7X13 FCM3BL (BL) | | 2 | 03 |
| | F15 | | Hexagonal Nut | 9S FCM33G | | ~ | 03 |
| | F16 | | Flat Washer | 9S FCM3BL | | | 01 |
| | F17 | | | A9S FNM33G | | | UI |
| | F18 | | Round Head Wood Screw | 2.7X13 FCM33G (CR) | | 2 | |
| | 1 10 | LA020000 | Noutiu Head Wood Sciew | 2.1 × 13 F CIVISSO (CR) | | 2 | |
| | G01 | 00477700 | Pickup Assembly | | F4 | | |
| <u> </u> | | | Pickup Assembly Pickup Escutcheon | lyon | Front | | |
| î | G01a | | | lvory | | | |
| | G03 G04 | VJ388800 | | 2.6X35 FCM3BL (BL) | | 2 | |
| * | | CB817760 | | | | | |
| * | G10 | | Pickup Assembly | hiomi | Rear | | |
| * | | QC473800 | | Ivory | | | |
| | G11 | CB817760 | Pickup Cushion | O OVOE FOMODI (EL) | | | |
| | G12 | VJ388800 | Round Head Wood Screw | 2.6X35 FCM3BL (BL) | | 2 | |
| | | | | | | | |
| | H01 | QC354400 | Accessory Unit (G-5) | | 1set | | 08 |
| | | | | | | | |
| * | | QC466600 | Bridge Assembly | TP6-3 (GOLD) | | | |
| | | | | | | | |
| ı | | Parte | · | 1 | RANK: | | |

* New Parts RANK:Japan only

WARNING: CHEMICAL CONTENT NOTICE!

The solder used in the production of this product contains LEAD. In addition, other electrical/electronic and/or plastic (where applicable) components may also contain traces of chemicals found by the California Health and Welfare Agency (and possibly other entities) to cause cancer and/or birth defects or other reproductive harm.


DO NOT PLACE SOLDER, ELECTRICAL/ELECTRONIC OR PLASTIC COMPONENTS IN YOUR MOUTH FOR ANY REASON WHAT SO EVER!

Avoid prolonged, unprotected contact between solder and your skin! When soldering, do not inhale solder fumes or expose eyes to solder/flux vapor!

If you come in contact with solder or components located inside the enclosure of this product, wash your hands before handling food.

■ CIRCUIT DIAGRAM

■ WIRING



■ SPECIFICATIONS

| - | CTANDADD | CDECTETCA TIONS |
|---|----------|-----------------|
| • | STANDARD | SPECIFICATIONS |

| • STILL BILLED ST ECHT TOTAL | |
|--|---|
| Scale Length628.6mm | |
| Body-Neck Construction ·····Bolt On | |
| Length979.0mm | |
| Width360.0mm | |
| Net Weight3.0kg | |
| • COLOR | |
| Body | |
| BLBlack | |
| OST-WBOrange Satin | |
| BS-WB ·····Brown Sunburst | |
| Neck | |
| BLBlack | |
| • BODY | |
| MaterialAlder, Spruce, Sycamore | |
| Body Depth47.0mm | |
| FINGERBOARD | |
| MaterialRosewood | |
| Fingerboard Width0-F 43.0 mm, 12-F 52.3 mm | 1 |
| No. of Frets22 | |
| • NECK | |
| MaterialMaple | |
| Neck Thickness1-F 20.9 mm, 12-F 23.1 mm | 1 |
| • PARTS | |
| HardwareGold Plated | |
| Nut ······Urea | |
| Bridge ·····TP6-3: Gold | |
| StringsXL-115 | |
| • CONTROLS | |
| Volume15A 500k ohm x 1 | |
| Tone05A 250k ohm x 1 | |
| Pickup SwitchToggle switch: Gold | |
| (3 position) | |
| • PICKUPS | |
| Front/ RearSmall Humbucking | |
| Magnet | |
| Front/RearAlnico | |
| | |